































If you need more details data sheet, Please send me E-mail, thank you

<p>Item No.: SR-01</p>	<p>Item No.: SR-02</p>	<p>Item No.: SR-03</p>	<p>Item No.: SR-04</p>
		<p>Note: plating 3U *gold current 1.5A stretch 1.0=115g Max stroke 1.8mm TH072</p>	<p>Note: plating 1U *gold current 1A stretch 1.0=60g Max stroke 1.8mm TH278</p>
<p>Item No.: SR-05</p>	<p>Item No.: SR-06</p>	<p>Item No.: SR-07</p>	<p>Item No.: SR-08</p>
<p>Note: plating 3U *gold current 3A stretch 1.5=360g Max stroke 3.2mm TH096</p>	<p>Note: plating 0U *gold current 3A stretch 4.0=260g Max stroke 5.5mm TH097</p>	<p>Note: plating 60U *MINNickel current 3A stretch 1.0=100g Max stroke 2.6mm TH170</p>	<p>Note: plating 60U *MINNickel current 3A stretch 2.0=200g Max stroke 4.5mm TH171</p>
<p>Item No.: SR-09</p>	<p>Item No.: SR-03</p>	<p>Item No.: SR-04</p>	<p>Item No.: SR-02</p>
<p>Note: plating 60U *MINNickel current 3A stretch 1.0=120g Max stroke 2.9mm TH172</p>	<p>Note: plating 2U *gold current 2.5A stretch 1.2=240g Max stroke 1.7mm TH179</p>	<p>Note: plating 20U *silver current 1A stretch 0.4=80g Max stroke 0.8mm TH180</p>	<p>Note: plating 3U *gold current 5A stretch 4.0=240g Max stroke 5.5mm TH259</p>
<p>Item No.: SR-05</p>	<p>Item No.: SR-14</p>	<p>Item No.: SR-15</p>	<p>Item No.: SR-16</p>

 <p>Note: plating 2U "gold current 5A stretch 1.5=240g Max stroke 3.0mm TH260</p>	 <p>Note: plating 2U "gold current 5A stretch 1.0=300g Max stroke 2.95mm TH268</p>	 <p>Note: plating 50U "MINNickel current 1A stretch 2.0=210g Max stroke 4.5mm TH270</p>	 <p>Note: plating 60U " MINNickel current 2A stretch 2.0=200g Max stroke 2.5mm TH301</p>
<p>Item No.: SR-17</p>	<p>Item No.: SR-18</p>	<p>Item No.: SR-19</p>	<p>Item No.: SR-20</p>
 <p>Lead Free Copper+Not Plating Max stroke 5.5mm Force: 260g+/-20g at 4.0mm</p>	 <p>Lead Free Copper+Plating 3U" gold Current 1A Max stroke 1.8mm Force: 150g+/-20g at 1.5mm</p>	 <p>Lead Free Copper+Not Plating Current 1A Max stroke 5.0mm Force: 240g+/-20g at 4.0mm</p>	 <p>Lead Free Copper+Not Plating Current 1A Max stroke 5.5mm Force: 600g at 2.0mm</p>
<p>Item No.: SR-21</p>	<p>Item No.: SR-22</p>	<p>Item No.: SR-23</p>	<p>Item No.: SR-24</p>
 <p>Copper+Plating Gold Current 1A Max stroke 3.2mm Force: 360g at 1.5mm</p>	 <p>Copper+Plating Gold 3U" Current 1A Max stroke 2.7mm Force: 400g at 2.5mm</p>	 <p>Copper+Plating Ni Current 1A Max stroke 1.8mm Force: 120g at 1.2mm</p>	 <p>Copper+Plating 1U" gold Current 1A Max stroke 2.8mm Force: 240g at 2.0mm</p>
<p>Item No.: SR-25</p>	<p>Item No.: SR-26</p>	<p>Item No.: SR-27</p>	<p>Item No.: SR-28</p>
 <p>Copper+Plating 3U" gold Current 5A Max stroke 3.0mm</p>	 <p>Copper+Plating 5U" gold Current 3A Max stroke 4.0mm</p>	 <p>Copper+Plating 3U" gold Current 1A Max stroke 1.3mm Force: 80g at 0.8mm</p>	 <p>Copper+Not Plating Current 1A Max stroke 5.5mm Force: 240g at 4.0mm</p>
<p>Item No.: SR-29</p>	<p>Item No.: SR-30</p>	<p>Item No.: SR-31</p>	<p>Item No.: SR-32</p>

If you need more details data sheet, Please send me E-mail, thank you

 <p>Copper+Plating 3U" gold Current 10A Max stroke 8.0mm Force: 500g at 5.0mm</p>	 <p>Copper+Plating 3U" gold Current 1A Max stroke 1.8mm Force: 100g at 0.8mm</p>	 <p>Copper+Plating 3U" gold Current 1A Max stroke 3.0mm Force: 50g at 2.5mm</p>	 <p>Copper+Plating Ni Current 1A Max stroke 2.5mm Force: 200g at 2.0mm</p>
<p>Item No.: SR-33</p>	<p>Item No.: SR-34</p>	<p>Item No.: SR-35</p>	<p>Item No.: SR-36</p>
 <p>Copper+Plating 2U" gold Current 1A Max stroke 1.7mm Force: 240g at 1.2mm</p>	 <p>Copper+Plating 1U" gold Current 1A Max stroke 8.3mm Force: 150g at 8.0mm</p>	 <p>Copper+Plating 3U" gold Current 10A Max stroke 1.5mm Force: 100g at 0.8mm</p>	 <p>Copper+Plating Gold Current 12A Max stroke 1.8mm Force: 350g at 1.5mm</p>
<p>Item No.: SR-37</p>	<p>Item No.: SR-38</p>	<p>Item No.: SR-39</p>	<p>Item No.: SR-40</p>
 <p>Copper+Plating 3U" gold Current 1A Max stroke 2.5mm Force: 120g at 1.5mm</p>	 <p>SUS304+Not Plating Current 1A Max stroke 2.5mm Force: 150g at 1.5mm</p>	 <p>Copper+Plating 1U" gold Current 3A Max stroke 1.8mm Force: 100g at 1.0mm</p>	 <p>Copper+Plating 3U" gold Current 3A Max stroke 5.5mm</p>
<p>Item No.: SR-41</p>	<p>Item No.: SR-42</p>	<p>Item No.: SR-43</p>	<p>Item No.: SR-44</p>
 <p>Plunger: White POM Barrel: Copper+Plating gold Max stroke 2.8mm Force: 120g at 1.5mm</p>	 <p>Copper+Plating Ni Current 1A Max stroke 1.8mm Force: 120g at 1.2mm</p>		
<p>Item No.: SR-45</p>	<p>Item No.: SR-46</p>		